

Spraymotion Macro FX Systems for 4D & Simulator Environments

Our **Spraymotion** Macro system allows sequencing of water effects (i.e. mists, sprays, spritzers) to outside controls, adding a capability of triggering in three independent zones. Perfect for spray or spritzer effects that are delivered in a “macro” environment where effects come from overhead, **Spraymotion** Macro Spray Ports can be grouped in a variety of configurations up to a maximum of 25 total spray ports.

The **Spraymotion** effects are triggered by outside controls using relay contact closures in the **Spraymotion** Controller. Timing of the sprays can be dictated by outside controls or set manually in the **Spraymotion** Controller for each zone.

The **Spraymotion** system is designed to allow for easy implementation so that spray and spritzer effects can be successfully installed by any integrator or designer.

Spraymotion Macro effects can scale to very large indoor or outdoor settings.

Specifications

Spraymotion System Controller Dimensions:	20" h x 18" w x 8" d 508mm h x 457mm w x 203mm d
Input Power:	120VAC
Power Consumption:	240 Watt
Control:	3 relay contact closures, one for each zone, built in timer and/or control by outside system
Number of Zones:	3 zones
Number of Spray Ports	25 total spray ports maximum
Water Supply Pressure Range:	40 - 80 psi
Macro Spray Port Angle:	60° @ 40 psi
Macro Spray Port Coverage:	Approximate 5' diameter (standard nozzle)
Macro Spray Port Flow Rate:	.57 gpm/2.16 lpm @ 40 psi
Macro Spray Port Inlet Connection:	1/4"
Warranty:	1 Year, Unlimited Customer Support



Spraymotion Macro spray port assembly

